



S8VK-C06024

Fuente de alimentación 60W/24V/2.5A carril DIN LITE

Especificaciones

Type	DIN-rail
Mounting method	DIN rail
Phase	Single
Output voltage	24 V
Power output	60 W
Rated output current	2.5 A
Temperature range	-25-60 °C
Terminal type	Screw
Communication port(s)	None
Alarm function	-
Number of output branches	1
Efficiency	88 %
Rated supply voltage at AC 50 Hz	100-240 V
Allowable supply voltage AC	85-264 V
Allowable supply voltage DC	90-350 V
Product Width (unpacked)	32 mm
Product Height (unpacked)	90 mm
Product Depth (unpacked)	110 mm

Productos relacionados:



Disyuntor electrónico

S8V-CP - Disyuntor electrónico

Descargas

Librería CAD



EAC Mark removal
Aviso de discontinuación

EN PDF 221 KB



Perfect Power Supply Solutions
Catálogo

ES PDF 810 KB



S8VK-C Switch Mode Power Supply
Datasheet

EN PDF 4,74 MB

TÉRMINOS DE USO DEL SITIO WEB

Este documento PDF se generó a partir del sitio web europeo de OMRON Industrial Automation el 12 November, 2025. Haga clic aquí para acceder a los [legal](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU